

350-501^{Q&As}

Implementing and Operating Cisco Service Provider Network Core Technologies (SPCOR)

Pass Cisco 350-501 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.lead4pass.com/350-501.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers





QUESTION 1

Which configuration modifies Local Packet Transport Services hardware policies?

- A configure
 Ipts police
 exception invalid rate 400
 protocol cdp rate 50
 protocol arp rate 5000
- B. configure
 Ipts pifib police hardware
 flow ospf unicast default rate 200
 flow bgp configured rate 200
 flow bgp default rate 100
 !
 Ipts pifib police hardware location 0/2
 flow ospf unicast default rate 100
 flow bgp configured rate 300
 flow icmp application rate 100
 !
- C. configure
 Ipts pifib hardware police
 flow ospf unicast default rate 200
 flow bgp configured rate 200
 flow bgp default rate 100
 !
 Ipts pifib hardware police location 0/2/CPU0
 flow ospf unicast default rate 100
 flow bgp configured rate 300
 flow icmp application rate 100
 flow icmp default rate 100
- D. configure
 Ipts punt police location 0/0/CPU0
 exception invalid rate 400
 protocol cdp rate 50
 protocol arp rate 5000
 protocol ipv4 options rate 100
 exception icmp rate 200

1

2021 Latest lead4pass 350-501 PDF and VCE dumps Download

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Correct Answer: C

 $Reference: https://www.cisco.com/c/en/us/td/docs/routers/crs/software/crs_r4-1/addr_serv/command/reference/b_ipaddr_cr41crs/b_ipaddr_cr41crs_chapter_0111.html#wp1754734006$

QUESTION 2

ip cef distributed mpls ldp graceful-restart interface GigabitEthernet 0/0/1 mpls ip mpls label protocol ldp

Refer to the exhibit Which effect of this configuration is true?

- A. R1 can support a peer that is configured for LDP SSO/NSF as the peer recovers from an outage.
- B. R1can support a graceful restart operation on the peer, even if graceful restart is disabled on the peer.
- C. R1 can failover to any peer.
- D. R1 can failover only to a peer that is configured for LDF SSO/NSF.

Correct Answer: A

Reference: https://www.cisco.com/en/US/docs/general/Test/kwoodwar/fsgr29s.html

QUESTION 3

Which BGP attribute is used first when determining the best path?

- A. origin
- B. AS path
- C. local preference
- D. weight



Correct Answer: D

QUESTION 4

Which statement about Network Services Orchestrator (NSO) is true?

- A. It must use SDN as an overlay for addressing.
- B. It uses YANG modeling language to automate devices.
- C. It is used only in service provider environments.
- D. It can be used only with XML coding.

Correct Answer: B

QUESTION 5

You are configuring MPLS traffic-engineering tunnels in the core. Which two ways exist for the tunnel path across the core? (Choose two.)

- A. The dynamic path option is supported only with IS-IS.
- B. Tunnels can be configured with dynamic path or explicitly defined path.
- C. A zero bandwidth tunnel is not a valid option.
- D. The bandwidth statement creates a "hard" reservation on the link.
- E. Tunnel links inherit IGP metrics by default unless overridden.

Correct Answer: BE

QUESTION 6

When configuring traffic engineering tunnels in Cisco MPLS core network, you see the traffic is not taking the expected path in the core.

Which command do you use to quickly check path of a TE tunnel?

- A. Traceroute mpls ipv4 -tunnel destination
- B. Ping
- C. show mpls traffic-engineering tunnels
- D. traceroute

Correct Answer: A

QUESTION 7


An engineer is trying to implement BGP in a multihomed architecture. What must the engineer configure to influence inbound path selection?

- A. A route map with WEIGHT attribute to control the inbound traffic.
- B. An offset list to set the metric for routes received from neighboring autonomous systems.
- C. An access list to identify traffic and enable it on both of the provider-facing interfaces.
- D. A route map with AS_PATH attribute to control the inbound traffic.

Correct Answer: D

QUESTION 8

Refer to the exhibit.



R101 is peering with R102 and R103, and R201 is peering with R202 and R203 using iBGP Labeled Unicast address families. The OSPF area 0 border routers are in a full iBGP Labeled Unicast mesh, and VPNv4 routes are exchanged directly between PE routers R101 and R201 through iBGP

Which address family-level configuration must be applied on ABR R102 on ABR R102 to support a Unified MPLS routing architecture with partitioned IGP domains?



- A. router bgp 65512
 address-family ipv4
 neighbor 172.16.0.5 route-reflector-client
 neighbor 172.16.0.5 send-label
 neighbor 172.16.0.11 route-reflector-client
 neighbor 172.16.0.11 send-label
 neighbor 172.16.0.12 route-reflector-client
- B. router bgp 65512
 address-family ipv4
 neighbor 172.16.0.5 route-reflector-client
 neighbor 172.16.0.5 next-hop-self all
 neighbor 172.16.0.5 send-label
 neighbor 172.16.0.11 next-hop-self all
 neighbor 172.16.0.12 send-label
 neighbor 172.16.0.12 send-label
- C. router bgp 65512
 address-family ipv4
 neighbor 172.16.0.5 route-reflector-client
 neighbor 172.16.0.5 next-hop-self all
 neighbor 172.16.0.11 next-hop-self all
 neighbor 172.16.0.12 next-hop-self all
- D. router bgp 65512 address-family ipv4 neighbor 172.16.0.5 route-reflector-client neighbor 172.16.0.5 next-hop-self neighbor 172.16.0.5 send-label neighbor 172.16.0.11 next-hop-self neighbor 172.16.0.12 send-label neighbor 172.16.0.12 send-label
- A. Option A
- B. Option B
- C. Option C
- D. Option D

Correct Answer: B

QUESTION 9

VCE & PDF Lead4Pass.com

https://www.lead4pass.com/350-501.html

2021 Latest lead4pass 350-501 PDF and VCE dumps Download

A network engineer is implementing BFD configuration changes on a customer\\'s equipment. How is the bfd interval configuration on the interface disconnected?

- A. The status of the interface changes.
- B. The IPv4 or IPv6 address configuration on the interface changes.
- C. It is automatically disconnected when the BFD-configured subinterface is removed.
- D. It is automatically disconnected when the BFD main interface is removed.

Correct Answer: D

QUESTION 10

A service provider has a requirement to deliver WAN gateway functionality to multi- tenant, provider-hosted clouds. Which cisco platform meets this requirement?

- A. Cisco ASR 9000 series
- B. Cisco NX-OS
- C. Cisco ASR 1000 Series
- D. Cisco CSR 1000v
- E. Cisco CRS series

Correct Answer: D

QUESTION 11

A customer of an ISP requests support to setup a BGP routing policy. Which BGP attribute should be configured to choose specific BGP speakers as preferred points for the customer AS?

- A. lowest multi-exit discriminator
- B. highest local preference outbound
- C. lowest local preference inbound
- D. highest local preference inbound

Correct Answer: B


QUESTION 12

DRAG DROP

Drag and drop the OSs from the left onto the correct descriptions on the right.


Select and Place:

Answer Area



Correct Answer:

Answer Area




QUESTION 13

DRAG DROP

Drag and drop the technologies from the left onto the correct definitions on the right.


Select and Place:

Answer Area



Correct Answer:

Answer Area



QUESTION 14

Refer to the exhibit.



```
ip cef distributed mpls ldp graceful-restart interface GigabitEthernet 0/0/1 mpls ip mpls label protocol ldp
```

What is the effect of this configuration?

- A. R1 supports a graceful restart operation on the peer, even if graceful restart is disabled on the peer.
- B. R1 supports a peer that is configured for LDP SSO/NSF as the peer recovers from an outage.
- C. R1 failovers only to a peer that is configured for LDP SSO/NSF.
- D. R1 failovers to any peer.

Correct Answer: C

QUESTION 15

```
PE-A#config t
PE-A(config) #class-map VOIP
PE-A(config-cmap) #match precedence 5
PE-A(config-cmap) #policy-map MARK-TRAFFIC
PE-A(config-pmap) #class VOIP
```

Refer to the exhibit. Which command is used to complete this configuration for QoS class-based marking?

- A. PE-A(config-pmap-c)#set dscp ef
- B. PE-A(config-pmap-c)#priority
- C. PE-A(config-pmap-c)#random-detect
- D. PE-A(config-pmap-c)#fair-queue



https://www.lead4pass.com/350-501.html 2021 Latest lead4pass 350-501 PDF and VCE dumps Download

Correct Answer: A

350-501 PDF Dumps

350-501 Practice Test

350-501 Study Guide



To Read the Whole Q&As, please purchase the Complete Version from Our website.

Try our product!

100% Guaranteed Success

100% Money Back Guarantee

365 Days Free Update

Instant Download After Purchase

24x7 Customer Support

Average 99.9% Success Rate

More than 800,000 Satisfied Customers Worldwide

Multi-Platform capabilities - Windows, Mac, Android, iPhone, iPod, iPad, Kindle

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

https://www.lead4pass.com/allproducts

Need Help

Please provide as much detail as possible so we can best assist you. To update a previously submitted ticket:





Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © lead4pass, All Rights Reserved.